



TRAILED SPRAYER WITH CENTRIFUGAL CANNON FAN UNIT



PRODUCT DESCRIPTION

The BW-TS series includes trailed sprayers with a cannon centrifugal air blower (TS), suitable for treatments on various medium-high crops, open fields, and greenhouses. The BW-TS allows precise interventions in difficult-to-access situations, even from a perimeter position

STANDARD EQUIPMENT

- Galvanized fixed drawbar with adjustable length
- **Hot galvanized chassis**
- **Low-profile main tank in high-density polyethylene (HDPE) with 9 mm thickness on 600/800/1000/1500 L versions**
- **Low-profile main tank in high-density polyethylene (HDPE) with 10 mm thickness on 2000/3000 L versions**
- Circuit rinsing and hand washing tank
- **Brass control unit with remote pressure regulator mounted on the tractor (Mod.BMS 50) ANNOVI REVERBERI**
- **ANNOVI REVERBERI brass pump**
- Hot-dip galvanized cannon unit and components
- **Single suction centrifugal air fan on TS 40, 2 speeds (V) + neutral (F).**
- **Double suction centrifugal air fan on TS 65, 2 speeds (V) + neutral (F)**
- **Cannon on Left side** (relative to rear PTO) with **0° to 90° rotation via hydraulic cylinder**
- **Deflector for under-row treatment.**
- Nozzle-holder arches in **stainless steel** and **brass anti-drip double-nozzles**
- Brass filter kit for nozzle holder arches (2 filters included)
- External suction filter with self-filling
- Internal Agitator
- Pesticide suction kit with external suction filter and self-filling
- Adjustable support wheel
- Standard galvanized lower tank protection **on the 1000 L version due to the tank's shape.**
- Adjustable support wheel
- Rear light and reflector kit
- Compliant with Regulation (EU) 2023/1230
- Road approval
- Tyres **225/60 - R15 - RADIAL - 5 fori** on **600/800 L** versions
- Tyres **10.0/80 - R12 - 10PR - 5-hole** pattern on **1000 L** version
- Tyres **13.0/55 - R16 - 14PR - 6-hole** pattern on **1500/2000 L** versions
- Tyres **285/70 - R19,5 - 6-hole** pattern on **3000 L** version
- Machine supplied without cardan shaft



CONFIGURATIONS

MODEL					
40 TS	440 mm	3+2	2V+F	A: 20 mt	B: 25-30 mt
65 TS	450 + 450 mm	6+3	2V+F	A: 30 mt	B: 35-40 mt

MODEL						CODE
40 TS - SINGLE SUCTION						
BW600 - 40TS	BHS90	90	40/50 hp	600 L	L235 - P115 - H120+55 cm	450 Kg ATO0587A-D
BW800 - 40TS	BHS90	90	40/50 hp	800 L	L250 - P120 - H120+55 cm	480 Kg ATO0588A-D
BW1000 - 40TS	BHS105	105	60/70 hp	1000 L	L290 - P134 - H128+50 cm	490 Kg ATO0589A-D
BW1500 - 40TS	BHS130	130	65/75 hp	1500 L	L325 - P148 - H133+45 cm	540 Kg ATO0590A-D
BW2000 - 40TS	BHS150	150	65/75 hp	2000 L	L340 - P160 - H140+30 cm	570 Kg ATO0591A-D
BW3000 - 40TS	BHS170	170	80/90 hp	3000 L	L365 - P190 - H150+10 cm	720 Kg ATO0592A-D
65 TS - DOUBLE SUCTION						
BW600 - 65TS	BHS90	90	70/80 hp	600 L	L260 - P115 - H120+80 cm	470 Kg ATO0532A-D
BW800 - 65TS	BHS90	90	70/80 hp	800 L	L275 - P120 - H120+80 cm	500 Kg ATO0533A-D
BW1000 - 65TS	BHS105	105	70/80 hp	1000 L	L305 - P134 - H128+75 cm	520 Kg ATO0430A-D
BW1500 - 65TS	BHS130	130	80/90 hp	1500 L	L340 - P148 - H133+60 cm	570 Kg ATO0534A-D
BW2000 - 65TS	BHS150	150	90/100 hp	2000 L	L355 - P160 - H140+55 cm	600 Kg ATO0458A-D
BW3000 - 65TS	BHS170	170	90/100 hp	3000 L	L380 - P190 - H150+35cm	750 Kg ATO0535A-D

ACCESSORIES ON REQUEST

	1	T40-900	T50-900	T50-1100
		CODE	CODE	CODE
		TRA0959	TRA0961	TRA1006
Cardan shaft				

	2	T40-900	T60-900	T60-1000	T60-1200
		CODE	CODE	CODE	CODE
		TRA1000	TRA0998	TRA0997	TRA1184
Homokinetic cardan shaft					

	3	CODE			
		COM0173			
		Brass Remote electric high-pressure control unit with pressure regulator on the frame (2 SECTIONS) BRAGLIA			

	4	CODE			
		COM0165			
		Brass Remote electric high-pressure control unit with pressure regulator on the tractor (2 SECTIONS) BRAGLIA			

	5	CODE			
		4S - COM0143			
		Electric control unit 4.0 / 5.0 High pressure - (2 SECTIONS) - BRAGLIA			



	6	CODE			
		COM0054			
		Electric control unit 4.0 / 5.0 High pressure - (2 SECTIONS) - ARAG			

	7	CODE			
		COM0024			
		Brass filter kit for nozzle holder arches (2 filters included)			

	8	CODE			
		ATO0556A			
		Galvanized lower tank protection (standard only on the 1000 L version due to the tank's shape)			



ACCESSORIES ON REQUEST

	9	600/800/1000 L	1500/2000 L	3000 L
		CODE	CODE	CODE
		ATO0119A-N	ATO0120A-N	ATO0221A-N
Autosteer adjustable drawbar (Maggio Steering) with tractor trailer hitch NOT APPROVED FOR ROAD CIRCULATION (Use in private areas, not road legal) See page 133				
	10	1500/2000 L	3000 L	
		CODE	CODE	
		ATO0678A	ATO0673A	
Autosteer drawbar with attachment to tractor lift arms NOT APPROVED FOR ROAD CIRCULATION (Use in private areas, not road legal) See page 133				
	11	600/800/1000 L	1500/2000 L	3000 L
		CODE	CODE	CODE
		ATO0119A	ATO0120A	ATO0221A
Autosteer adjustable drawbar (Maggio Steering) with tractor trailer hitch APPROVED FOR ROAD CIRCULATION only with Maggio SRL sprayers- See page 133				
	12	600 a 2000 L	3000 L	
		CODE	CODE	
		ATO0555A	ATO0695A-D	
Additional cost for hydraulic axle lifting system NOT APPROVED FOR ROAD USE (Use in private areas only, not road legal)				
	13	CODE		CODE
		COM0187		COM0188
Supplement for the out-of-square treatment system allowing adjustment of the cannon air outlet for off-trajectory spraying via hydraulic cylinder kit (65 TS only)		Supplement for 180-degree right/left rotation kit with turntable support and hydraulic gear motor (65TS only)		
	15	CODE		
		IRR0523		
90° fan spray air outlet with 0°/90° hydraulic rotation for complete coverage of dense and tall canopies using lateral and upper nozzles (65 TS only)				
	16	CODE		
		IRR0528		
Supplement for FLEX air tube kit with hydraulic motor and 0-270° turntable rotation, 0-90° hydraulic cylinder inclination. The system allows use in difficult situations, enabling the treatment flow to be directed to the precise target area (65 TS only)				
	17	CODE		CODE
		ATO0405A		COM0176
Extension kit with deflector used to increase air/spray flow range (65TS only)		LED Light kit for treatments in low-light conditions		
	19	CODE		
		COM0182		
Supplement for electrostatic charging system. The system improves treatment coverage				

